

NANOFARB

ON STANDART 3

Water-dispersion matte facade paint



- IDEAL FOR BUDGET-FRIENDLY RENOVATION
- WEATHER-RESISTANT
- LIGHT-FAST

PURPOSE

Matte water-dispersion paint for decorative exterior facade painting. Compatible with most mineral building substrates and wood. Neutral odour.

APPLICATION

Mix thoroughly before use. For the first coat, the material may be diluted with water up to 3% to adjust consistency. Apply by brush, roller or spray gun. Apply at least two coats using the "wet-on-wet" method, without pressing hard on the tool. For rough-textured surfaces, use a long-pile roller. Do not apply the paint to surfaces exposed to direct sunlight, strong wind, or precipitation; protect from precipitation until fully dry (at least 24 hours). Work at a substrate and air temperature of +5°C to +30°C and relative humidity below 65%.

SUBSTRATE

Level the surface and remove dirt, dust and efflorescence. Remove old, cracked and flaking coatings. The surface must be firm, smooth, dry and clean. New lime-cement surfaces must cure for at least 1 month. Treat with DeepPrime concentrate primer according to instructions; treat old, loose, highly absorbent mineral substrates with DeepFix primer. Surfaces affected by moss, mould or fungi should first be cleaned and treated with an antiseptic agent.

TINTING

Can be tinted with water-based colouring pastes or by machine tinting using the COLOR SYSTEM. Base A is intended for use as a stand-alone white coating, or for tinting into pastel, light shades.

COMPOSITION

Styrene-acrylic dispersion, ground marble, titanium dioxide, processing additives, isothiazolinone-based biocide, water. Contains no organic solvents, non-toxic, non-flammable. VOC content (subcategory A/3): 75 g/l (from 2021), 40 g/l (from 2024). This product contains <40 g/l VOC.

DRYING TIME

Before applying the next coat — approximately 1-2 hours. Fully dry in 12 hours at +20°C and 65% relative humidity. Full strength and resistance to mechanical load — after 7 days.

COVERAGE

Depending on the substrate, 170-210 g/m². The exact coverage is determined by a test application on-site.

SAFETY MEASURES

Wear protective goggles when spraying. Ensure thorough ventilation during application and drying. Avoid eating, drinking and smoking while using the paint. In case of contact with eyes or skin, rinse immediately with plenty of water.

STORAGE

In the sealed original container at a temperature of +5 to +35°C, out of reach of children. Protect from direct sunlight and heating appliances. Shelf life in a sealed original container — 24 months. Do not store once diluted.

DISPOSAL

Do not discharge into drains or waterways. Do not allow to enter soil. Dispose of in accordance with official regulations. Only empty containers may be recycled. Dried residues may be disposed of with household waste.

PACKAGING

Base A: 1.2 kg; 3 kg; 6 kg; 12 kg.

MANUFACTURED IN: UKRAINE, ODESSA, NOVOMOSKOVSKAYA ROAD 9
NANOFARB LLC · +380957887799 · WWW.NANOFARB.UA

Document version: 1.0 (draft)
Date: 10.09.2026

THIS TECHNICAL INFORMATION IS BASED ON THE CURRENT STATE OF THE ART AND OUR APPLICATION EXPERIENCE. HOWEVER, GIVEN THE VARIETY OF SUBSTRATES AND SITE CONDITIONS, THE BUYER/USER IS NOT RELIEVED OF THE OBLIGATION TO CHECK OUR MATERIALS AT THEIR OWN RESPONSIBILITY FOR SUITABILITY FOR THE INTENDED PURPOSE UNDER THE RELEVANT SITE CONDITIONS. NO LEGAL OBLIGATIONS CAN BE DERIVED FROM THE INFORMATION ABOVE. THIS DOCUMENT BECOMES INVALID UPON PUBLICATION OF A NEW EDITION.