

NANOFARB

ON STANDART PRIME

Deep-penetrating acrylic primer



- READY TO USE
- STRENGTHENS MINERAL SURFACES
- FOR INTERIOR AND EXTERIOR USE

PURPOSE

Ready-to-use deep-penetrating acrylic primer. Strengthens mineral surfaces, reduces and equalises their water absorption, and removes dust before plastering, filling, tiling, wallpapering or painting with water-dispersion paints. Improves adhesion of finishing materials and extends the service life of the whole paint system. For interior and exterior use.

APPLICATION

Ready to use, does not require dilution with water.

DRYING TIME

2–4 hours (+20°C, 60% relative humidity).

COMPOSITION

Water, aqueous acrylic copolymer. Contains 1,2-benzisothiazol-3(2H)-one (CAS 2634-33-5) and a reaction mixture of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (CAS 55965-84-9) — may cause an allergic skin reaction (EUH208).

COVERAGE

110–200 g/m², depending on the substrate and its water absorption.

SAFETY MEASURES

Contains components that may cause an allergic skin reaction (EUH208). Avoid contact with skin and eyes.

STORAGE

24 months at a temperature of +5 to +35°C. Protect from freezing.

PACKAGING

Plastic containers: 5 L; 10 L.

MANUFACTURED IN: UKRAINE, ODESSA, NOVOMOSKOVSKAYA ROAD 9
NANOFARB LLC · +380957887799 · WWW.NANOFARB.UA

Document version: 1.0 (draft)
Date: 10.09.2026

THIS TECHNICAL INFORMATION IS BASED ON DATA PUBLISHED BY THE MANUFACTURER AT WWW.NANOFARB.UA. GIVEN THE VARIETY OF SUBSTRATES AND SITE CONDITIONS, THE BUYER/USER IS NOT RELIEVED OF THE OBLIGATION TO CHECK THE MATERIALS AT THEIR OWN RESPONSIBILITY FOR SUITABILITY FOR THE INTENDED PURPOSE UNDER THE RELEVANT SITE CONDITIONS. NO LEGAL OBLIGATIONS CAN BE DERIVED FROM THE INFORMATION ABOVE.