

NANOFARB

ON STANDART FIX

Deep-penetrating primer concentrate (1:10)



- 1:10 CONCENTRATE
- FOR INTERIOR AND EXTERIOR USE
- REDUCES AND EQUALISES WATER ABSORPTION

PURPOSE

Primer concentrate for preparing external and internal mineral surfaces prior to finishing works: levelling with plaster, filling, tiling or installing gypsum boards, laying floors, wallpapering, installing thermal insulation, etc. Reduces and equalises the substrate's water absorption, removes dust and strengthens it.

APPLICATION

Diluted with water before use — the concentrate allows you to adjust the dilution ratio yourself depending on the strength and density of the substrate. Do not apply undiluted concentrate.

DRYING TIME

4 hours (+20°C, 60% relative humidity).

COMPOSITION

Water, aqueous acrylic copolymer. Contains 1,2-benzisothiazol-3(2H)-one (CAS 2634-33-5) — may cause an allergic skin reaction (EUH208).

COVERAGE

110–200 g/m², depending on the substrate (concentrate, before dilution).

SAFETY MEASURES

Wear protective gloves and eye/face protection. Contains a component that may cause an allergic skin reaction (EUH208).

STORAGE

24 months in sealed original packaging, at a temperature of +5 to +35°C.

PACKAGING

1 L container (1:10 concentrate).

MANUFACTURED IN: UKRAINE, ODESSA, NOVOMOSKOVSKAYA ROAD 9
NANOFARB LLC · +380957887799 · WWW.NANOFARB.UA

Document version: 1.0 (draft)
Date: 10.09.2026

THIS TECHNICAL INFORMATION IS BASED ON DATA PUBLISHED BY THE MANUFACTURER AT WWW.NANOFARB.UA. GIVEN THE VARIETY OF SUBSTRATES AND SITE CONDITIONS, THE BUYER/USER IS NOT RELIEVED OF THE OBLIGATION TO CHECK THE MATERIALS AT THEIR OWN RESPONSIBILITY FOR SUITABILITY FOR THE INTENDED PURPOSE UNDER THE RELEVANT SITE CONDITIONS. NO LEGAL OBLIGATIONS CAN BE DERIVED FROM THE INFORMATION ABOVE.